



Overview

The E15's extended bottom end can easily cover many club applications on its own, when used with the processor and a subwoofer, it can be the ideal mid-high loudspeaker cabinet. The E15 can be utilized vertically or horizontally and comes equipped with flypoints and recessed standmount adaptor for maximum versatility.

The rotatable 80° x 50° horn means high frequency dispersion can be tailored to suit the cabinet's placement.

Integrated flypoints and standmount adaptor means the E15 can be flown or stage-mounted in used as a front-of-house box or stage monitor in any installation, touring or club rig.

The unique cabinet shape makes for tighter arrays and the ability to fly the cabinet much closer to walls and ceilings than most conventional boxes. When used with the EP1215 processor, the E15 can be easily bi-amplified, or used with any élite series subwoofer.

E15 - Black Ozite (Carpet) Finish

E15B - Black Ultrathane (Painted) Finish

Features

- 1400 Watt Full Range Loudspeaker (700 Watts Program)
- 15-inch Woofer / 1-inch Compression Driver
- Max SPL Peak 133dB (130dB Continuous)
- Designed for Front-of-House or Monitor applications
- 80° x 50° ABS Rotatable Custom Waveguide Horn
- Advanced PTC™ High Frequency Driver Protection
- 2 x Speakon™ and 2 x 1/4-inch Parallel Inputs
- Integrated All Metal Speaker Standmount Adaptor
- 5/8-inch (15mm) Birch Plywood Construction
- Made in Canada





Specifications

| | |
|------------------------------------|---|
| System Type | Multi Application Loudspeaker |
| Active or Passive | Passive |
| Program Power (Watts) | 700 Watts (1400 Watts Peak / 450 Watts Continuous) |
| Biampable | Yes |
| Nominal Impedance (Ohms) | 8 |
| Sensitivity (dB @1Watt/1m) | 100 |
| Max SPL (dB) | 133dB Peak (130dB Continuous) |
| Frequency Response (Hz +/- 3dB) | 55 - 26k |
| Crossover Frequency (Hz) | 1900 |
| Driver Configuration | 15-inch / 1-inch |
| HF Driver(s) | 1-inch throat (1.5-inch voicecoil) |
| HF Horn | ABS plastic custom Waveguide |
| HF Dispersion (°H x °V) | 80 x 50 (Rotatable) |
| HF Protection | PTC™ |
| LF Driver(s) | 15-inch (3-inch voicecoil) |
| Inputs - 1/4" Jacks | 2 |
| Inputs - Speakon 4-pin | 2 |
| Flying Hardware | 3/8-inch x 3 (2 Top, 1 Black) |
| Bar Handles | Two |
| Pole Mount Adapter (1 3/8" -3.5cm) | Yes |
| Enclosure Materials | 15mm (5/8inch) 11-ply Russian Birch |
| Grille | Perforated metal |
| Covering / Finish | Black Ozite (Carpet) |
| Optional Covering / Finishes | Black Ultrathane Paint (E15B) |
| Processor (optional) | EP1215 / EP1 |
| Dimensions (DWH xbackW COM inches) | 15 x 19 x 28.5 x 8 |
| Dimensions (DWH xbackW COM cm) | 38.5 x 46 x 73 x 21 |
| Weight (lbs/kg) | 54.7 / 24.8 |

Specifications subject to change without notice