

NX55P-2

12-INCH POWERED LOUDSPEAKER



Overview

The NX55P-2 trapezoid box is ideal for mounting in arrays, or for use as a monitor cabinet with well-protected inputs and controls. Designed for maximum versatility, the NX55P-2 can be used in any orientation, including close to walls, floors and in close arrays with multiple cabinets.

The NX55P-2 has a built-in mixer which allows the loudspeaker to be used directly with a microphone and / or line source. The loop output allows additional active cabinets to be driven from one cabinet's mixer stage, or a series of cabinets to be driven from one source.

Features

- 2000 Watts (Peak) 1000 Watts (Program)
- 12-inch woofer with 3-inch voice coil
- 1.4-inch compression driver
- 80° x 50° HF dispersion
- Multi-input source mixer
- Molded Polypropylene cabinet construction
- Bi-amped power module
- Made in Canada



Specifications

System Type	2-way
Powered or Passive	Powered
Program Power (watts)	2000 watts peak 1000 watts program
Max SPL (dB)	128dB continuous
Frequency Response (Hz +/- 3dB)	45 - 18k (Hz +/-3dB)
Crossover Frequency (Hz)	2kHz
LF Woofer	12"
HF Driver(s)	1.4" (1-inch exit)
HF Dispersion (°H x °V)	80° x 50°
Power Cable	Yes (Detachable IEC)
Mixer Controls	Mixer on/off switch Mic Input Gain Line Input Gain Treble/Bass Tweak
Level Controls	Main Volume
EQ Controls	100Hz HP Filter (LF Rolloff)
Inputs (1/4")	2 (line input) 2 (link in/out)
Inputs (XLR)	1 (mic) 2 (line in/out)
Flying Hardware	2 x Top, 2 x Bottom, 1 x Pullback 1/4-20 Threading
Optional Flying Hardware	NXF Flyware
Bar Handles	1 x Side
Pole Mount Adapter (1 3/8-inch/3.5cm)	1 Bottom
Enclosure Materials	Molded Polypropylene
Grille	Powdered Coated Perforated Steel
Dimensions (DWH x backW, inches)	12.25 x 16 x 26.5 x 9
Dimensions (DWH x backW, cm)	31.12 x 40.6 x 67.3 x 22.9
Weight (lbs/kg)	41 / 18.6
Box Dimensions (LxWxH, inches)	16.5 x 12.6 x 28.3
Box Dimensions (LxWxH, cm)	42 x 32 x 72

Specifications subject to change without notice

