

# YSM6-2

6.5-INCH POWERED STUDIO MONITOR



## Overview

Yorkville Sound's YSM SERIES 2 Powered Studio Monitors are engineered to deliver the uncompromising clarity your mixes demand. Designed with project and professional studios in mind, the YSM6-2 has been developed to be the best sounding monitor in its class.

The YSM6-2 features 1-inch silk diaphragm neodymium dome tweeters. These tweeters blend seamlessly into the specially designed low diffraction wave guide which is integrated into the front baffle. The edges of the wave-guide perfectly couple the tweeter with the woofer, reducing sonic anomalies normally associated with driver/tweeter proximity.

The woofer and tweeter have been perfectly time aligned to eliminate any phase irregularities usually associated with 2-way designs.

## Features

- 75 Watts
- 6.5-inch woofer
- 1-inch Silk Neodymium dome tweeter
- High and Low Frequency adjust controls
- Volume Control

## Specifications

System Type	2-way
Powered or Passive	Powered
Program Power (watts)	75 watts
Max SPL (dB)	105dB continuous
Frequency Response (Hz +/- 3dB)	45 - 22k (Hz +/-3dB)
Crossover Frequency (Hz)	2.1KHz
LF Woofer	6.5"
HF Driver(s)	1" Silk Neodymium dome
Power Cable	Yes (Detachable IEC)
Level Controls	Volume
EQ Controls	HF and LF Adjust
Inputs	1 x 1/4" TRS Balanced 1 x XLR Balanced 1 x RCA Unbalanced
Enclosure Materials	MDF ABS Baffle
Covering / Finish	Textured Vinyl
Dimensions (DWH xbackW, inches)	10 x 9.5 x 15
Dimensions (DWH xbackW, cm)	25.4 x 24.13 x 38.1
Weight (lbs/kg)	15 / 6.8
Box Dimensions (LxWxH, inches)	14 x 13.4 x 19.3
Box Dimensions (LxWxH, cm)	35 x 34 x 49

Specifications subject to change without notice

